

## Cradle-PERF

The **Cradle-PERF** module applies user-defined calculations to an architecture model, to compare the performance of alternative architectures and apportion performance budgets to subsystem, component and equipment designs.

Simulation is an activity to reproduce a system's behavior in an artificial environment to test the system in a variety of scenarios. Simulation is used where testing the real system is either dangerous, impracticable or too time-consuming or expensive.

The most fundamental behavioral characteristics of systems are set early in the design process, as alternative architecture topologies are assessed and performance budgets are set. But as there is no behavior allocated to the components, it is not possible to build a simulation.

Performance assessment solves this problem. It is used before behavior is known and allocated and so before simulation can be used. It can be used to confirm if a proposed architecture is viable. It can be used to compare performance characteristics of candidate architectures. It can be used to define budgets for lower design levels (apportionment). Later, it can be used to aggregate actual values.

Performance assessment is expressed in userdefined characteristics, typically concerned with timing, data error or precision, such as:



They can be subdivided, for example to study best case, worst case and typical conditions. They are held as user-defined formulae in the specifications and data definitions of the symbols in the diagrams of the architecture models.

Any number of performance characteristics can be defined and associated with each diagram symbol. Each has its own formula. These are defined using a function library and user-defined calculation routines. This library contains logical, arithmetic, logarithmic, exponential, ladder, table lookup and interpolation routines, amongst others.

## System performance

requirements are applied as constraints to these characteristics by linking the items in the database and defining ranges of values for the performance characteristics that should not, or may not, be exceeded.

Analyses are run on state models that are sets of interconnected diagrams at appropriate levels in the architecture.

A state model can have external loads applied to it to represent different usage scenarios. An analysis can contain many such environmental loads. The environmental loads are defined as values of any of the performance characteristics at the external input(s) to the model.



Each analyses applies the environment load and calculates performance characteristics for all of the symbols in the state model's diagrams using the formulae and constraints in each symbol. The results are therefore quantitative. They are stored inside the symbols' descriptions.

The results can be reported in the same manner as other information in a Cradle database. They can also be graphed. The graphs will typically show the values of specified characteristics along a path through the

PERF Performance Modelling

> SO 9909 SOQAR RECETTERD Certificate Number 162/5

RC014/18 Date: February 2023 © 3SL Cradle is a registered trademark of 3SL in the UK and other countries. All rights reserved. All other trademarks are the property of their respective owners.

**Cradle-7** 

From concept to creation.

http://www.threesl.com salesdetails@threesl.com support@threesl.com Structured Software Systems Ltd (3SL) Suite 2, 22a Duke Street Barrow-in-Furness Cumbria LA14 1HH, UK Tel: +44 (0) 1229 838867 Fax: +44 (0) 1229 870096 Regd: 2153654 VAT: GB 473 2757 28

model, termed a thread.

Each graph will show any



constraints applied from the system requirements and the effect of the constraints on the analysis results. The data in such



graphs can be exported to CSV.

Any number of such thread analyses can occur.

The results will show that an architecture is viable if none of its constraints are violated.

Since the performance data is built into the architecture model, any and all changes to the model's topology (such as a change to the architecture) will be automatically reflected in changes to the performance results. This allows easy comparison between alternative architectures.

The analysis results are the characteristics of a viable architecture. Hence, they are the constraints or budgets for the next level of design. So the analysis of each level produces performance constraints for the next level. This process can continue through the design levels until the system behavior is sufficiently well defined for simulation to be practicable.



| Feature   | Benefits  |
|---|---|
| Performance assessment based on<br>characteristics of system behavior | Can be used before behavior is decided or functions allocated to identify performance budgets   |
| Predictive tool   | Defines constraints on each design level from the level above it  |
| Arbitrary subdivision of<br>characteristics                           | Study multiple situations and contexts simultaneously, such as best case, worst case, and typical case  |
| Budget apportionment  | Allocate budgets hierarchically downwards   |
| Result aggregation  | Aggregate results from lower levels to the higher levels  |
| Constraint assignment   | Limiting and advisory constraints to impose acceptance criteria and performance requirements on analyses  |
| Arbitrarily extensible  | Add any number of performance characteristics to analyses   |
| Extensive function library  | Pre-defined functions for all common operations including table lookups, step or ladder functions, linear interpolations, and linear, exponential and logarithmic expressions |
| Access to external functions and<br>simulations                       | Embed any external calculation or simulation routine for complete flexibility   |
| Multi-layer environmental effects                                     | Build environment loads using a flexible three-tier approach, to test system failure conditions and explore maximum load criteria   |
| Define models for analysis  | Define appropriate architectures or subsets of architectures for study at any level of detail   |
| Multiple analysis results held within the design                      | Allows comparative assessments of alternative architectures or alternative function allocations to, or within, subsystems   |
| Change to the model change the performance                            | Any change to the topology of the architecture model will directly affect its performance characteristics without any need to change the performance analysis                 |
| Graphical output  | Visually presents performance characteristics along threads for easy understanding of performance throughout the system   |
| Cross referenced to entire database                                   | Linked to performance requirements and acceptance criteria  |



Structured Software Systems Ltd (3SL) Suite 2, 22a Duke Street Barrow-in-Furness Cumbria LA14 1HH, UK Tel: +44 (0) 1229 838867 Fax: +44 (0) 1229 870096 Regd: 2153654 VAT: GB 473 2757 28 RC014/18 Date: February 2023 © 3SL Cradle is a registered trademark of 3SL in the UK and other countries. All rights reserved. All other trademarks are the property of their respective owners.

> http://www.threesl.com salesdetails@threesl.com support@threesl.com